

73

DEPENDENT RESURVEY OF THE
SIXTH STANDARD PARALLEL NORTH,
THROUGH RANGE 46 EAST, MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE
SIXTH STANDARD PARALLEL NORTH,
THROUGH RANGE 46 EAST, MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
A. J. Hatch, J. H. Eaton and J. C. Smyles
U. S. Deputy Surveyors, in 1872, and
the Resurvey Executed by
S. T. Morse, U. S. Deputy Surveyor,
in 1901, and the Resurvey Executed by
W. A. Pray, U. S. Surveyor,
in 1914.

From the standard cor. of Tps. 30 and 31 N., R. 46 E.,
monumented with a basalt stone, 20x12x8 ins., firmly set
in a mound of stone, plainly mkd. with 6 grooves on the
N., S. and W. faces; 46 E. on the W. face; 30 N. on the
S. face, and SC 31 N on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

S C
T31N|T31N
R46E|R47E
S 36|
S 1|S 31
T30N|

1981

Deposit the original cornerstone and set a steel fence
post, 5½ ft. long, alongside the aluminum post and
rebuild the mound of stone, 3 ft. base, 2 ft. high, W.
of cor.

From this corner, the cor. of Tps. 30 and 31 N., R. 47
E., bears S. 0° 03' E., 2.60 chs. dist., monumented with
a basalt stone, 16x12x12 ins., firmly set in a mound of
earth, plainly mkd. with 6 grooves on the N., S. and E.
faces, CC R47 E on the E. face, 31 N on the N. face and
30 N on the S. face.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

|T31N
|R47E
T30N|S 31
R47E S 6

1981