

79

DEPENDENT RESURVEY OF THE
SIXTH STANDARD PARALLEL NORTH,
THROUGH RANGE 46 EAST, MDM, NEVADA

CHAINS	
	<p>Deposit the original cornerstone alongside the aluminum post and reset the RLS iron pin inside the aluminum post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 46' W., beginning new measurement.</p> <p>Over nearly level land.</p>
1.20	Draw, drains NW.
40.13	<p>The standard cor. of Tp. 31 N., Rs. 45 and 46 E., monumented with an iron post, 2½ ins. diam., firmly set showing 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North, through Range 45 East, executed under Group No. 439.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 31 N., R. 46 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by A. J. Hatch, J. H. Eaton and J. C. Smyles, U. S. Deputy Surveyors, in 1872, and the Survey and Resurvey Executed by E. H. Thurtell, U. S. Deputy Surveyor, in 1902.</p> <hr/> <p>From the standard cor. of Tps. 30 and 31 N., R. 46 E.</p> <p>N. 0° 03' W., along the E. bdy. of sec. 36.</p> <p>Over rolling land, covered with scattered sagebrush.</p>
37.46	<p>The W ¼ sec. cor. of sec. 31, T. 31 N., R. 47 E., monumented with a basalt stone, 10x10x6 ins., firmly set in a mound of stone, plainly mkd. ¼ on the W. face, with RLS tag No. 4233 wired to the cornerstone.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T31N R46E R47E ¼ S 31</p> <p style="text-align: center;">1981</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post and rebuild the mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/>