

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 31 N., R. 46 E., MDM, NEVADA

CHAINS	
2.60	<p>The cor. of secs. 1 and 12, monumented with a basalt stone, 14x10x5 ins., firmly set in a mound of stone, plainly mkd. with 5 notches on the S. edge and 1 notch on the N. edge.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T31N R46E R47E S 1 S 6 S 12 </p> <p style="text-align: center;">1981</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>N. 0° 25' W., along the E. bdy. of sec. 1.</p> <p>Over rolling land, covered with scattered sagebrush.</p>
31.30	<p>Improved gravel road, bears NE. and SW.</p>
37.42	<p>The W ¼ sec. cor. of sec. 6, T. 31 N., R. 47 E., monumented with a basalt stone, 18x16x4 ins., firmly set in a mound of stone, mkd. ¼ on the W. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T31N R46E R47E   ¼   S 6</p> <p style="text-align: center;">1981</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post and rebuild the mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p>
	<p>N. 0° 16' W., beginning new measurement.</p> <p>Over rolling land.</p>
2.63	<p>The E ¼ sec. cor. of sec. 1, monumented with a conglomerate stone, 24x18x6 ins., loosely set in a mound of stone, dimly mkd. ¼ on the W. face.</p> <p>At the corner point</p>