

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 31 N., R. 46 E., MDM, NEVADA

CHAINS

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T31N
R46E R47E
 $\frac{1}{4}$ |
S 1 |

1981

Deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. $0^{\circ} 13'$ W., beginning new measurement.

Over rolling land.

41.16

The cor. of T. 31 N., Rs. 46 and 47 E., monumented with a limestone, 24x18x12 ins., loosely set in a mound of stone, plainly mkd. with 6 grooves on the E., W. and S. faces.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, with aluminum cap mkd.

T32N R47E
S 31
S 1 | S 6
T31N | T31N
R46E | R47E

1981

Deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.

From this corner, the cor. of Tps. 32 N., Rs. 46 and 47 E., bears N. $89^{\circ} 42'$ W., 3.21 chs. dist., hereinafter described.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 31 N., R. 46 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
A. J. Hatch and J. H. Eaton, U. S. Deputy Surveyors,
in 1869, and the Resurvey Executed by
H. B. Maxson, U. S. Deputy Surveyor, in 1893, and
the Resurvey Executed by
E. H. Thurtell, U. S. Deputy Surveyor,
in 1902.