

93

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 31 N., R. 46 E., MDM, NEVADA

CHAINS

Deposit the unmarked stone and set a steel fence post, 5½ ft. long, alongside the aluminum post.

S. 89° 55' W., bet. secs. 3 and 34.

Over nearly level land, covered with scattered sagebrush.

29.90 Powerline, bears N. 1½° E. and S. 1½° W.

31.50 Improved gravel road, parallels powerline.

40.31 Point for the ¼ sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} \text{T32N R46E} \\ \text{S } 34 \\ \hline \frac{1}{4} \\ \text{S } 3 \\ \text{T31N} \end{array}$$

1981

Set a steel fence post, 5½ ft. long, alongside the aluminum post.

80.62 The cor. of secs. 3, 4, 33 and 34, monumented with an iron pin ½ in diam., with tag mkd. RLS No. 4233 wired to the iron pin, firmly set showing 4 ins. above the ground, at a fence corner, from which fences bear S. and W. This is accepted as a careful and faithful perpetuation of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} \text{T32N R46E} \\ \text{S } 33 | \text{S } 34 \\ \hline \text{S } 4 | \text{S } 3 \\ \text{T31N} \end{array}$$

1981

Reset RLS iron pin inside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
T. 31 N., R. 46 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
A. J. Hatch, J. H. Eaton and J. C. Syles,  
U. S. Deputy Surveyors, in 1872, and  
the Resurvey and Survey Executed by  
E. H. Thurtell, U. S. Deputy Surveyor,  
in 1902.