

179

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 37 N., R. 46 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 37 N., R. 46 E., MOUNT DIABLO, NEVADA

Reestablishment of a portion the Survey Executed by
A. J. Hatch, J. H. Eaton and J. C. Smyles,
U. S. Deputy Surveyors, in 1872

From the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented with
a basalt stone, 14x10x8 ins., plainly mkd. $\frac{1}{4}$ on the W.
face, loosely set in a mound of stone.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

T37N
R46E R47E
 $\frac{1}{4}$
S 12|S 7

1981

Deposit the original cornerstone and set a steel fence
post, $5\frac{1}{2}$ ft. long, alongside the aluminum post and raise
a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

N. $0^{\circ} 30'$ E., bet. secs. 7 and 12.

Over high rolling mountainous land, covered with
sagebrush and native grass.

32.00 Ridge, bears E. and W.

39.14 Point for the cor. of secs. 1, 6, 7 and 12, at
proportionate distance; there is no remaining evidence
of the original corner.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

T37N
R46E R47E
S 1|S 6
S 12|S 7
1981

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of
cor.

N. $0^{\circ} 30'$ E., bet. secs. 1 and 6.