

190

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,  
T. 38 N., R. 47 E., MDM, NEVADA

CHAINS	DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 38 N., R. 47 E., MOUNT DIABLO, NEVADA
	<hr/> <p>Reestablishment of the Survey Executed by T. K. Stewart, U. S. Deputy Surveyor, in 1884.</p> <hr/>
	<p>From the cor. of Tps. 37 and 38 N. and Rs. 47 and 48 E., monumented with an iron post, 3 ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 38 N., R. 48 E., executed under Group No. 114. This cor. is located in a fence cor., from which fences bear E. and SSW. This cor. is identical with a U.S.G.S. triangulation station.</p>
	<p>S. 88° 34' W., bet. secs. 1 and 36.</p>
	<p>Over rolling land, covered with sagebrush and native grass.</p>
40.40	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	$\begin{array}{r} \text{T38N R47E} \\ \text{S } 36 \\ \hline \frac{1}{4} \text{S } 1 \\ \text{T37N} \\ 1981 \end{array}$
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
80.80	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p>
	$\begin{array}{r} \text{T38N R47E} \\ \text{S } 35   \text{S } 36 \\ \hline \text{S } 2   \text{S } 1 \\ \text{T37N} \\ 1981 \end{array}$
	<hr/> <p>S. 88° 34' W., bet. secs. 2 and 35.</p>