

DEPENDENT RESURVEY OF A PORTION  
OF THE SUBDIVISIONAL LINES,  
T. 38 N., R. 47 E., MDM, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T38N R47E  <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> <math>\frac{3}{10}</math></p> <p style="text-align: center;">1981</p> <hr/> <p>N. 88° 56' W., beginning new measurement.</p> <p>Over meadowland.</p>
21.70	Willow Creek, 40 lks. wide, 3 ft. deep, course SW.
40.80	The cor. of secs. 3, 4, 9 and 10.
	<hr/> <p>N. 1° 24' W., bet. secs. 3 and 4.</p> <p>Over gently rolling land, covered with sagebrush and native grass.</p>
15.00	Trail road, bears ENE. and WSW.
16.00	Irrigation ditch, 20 lks. wide, 2 ft. deep, drains WSW.
38.40	Fence, bears E. and W.
41.02	The ¼ sec. cor. of secs. 3 and 4, monumented with a trap stone, 12x5x3 ins., dimly mkd. ¼ on the W. face, loosely set in a mound of earth.
	<p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T38N R47E  <math>\frac{1}{4}</math>  S 4   S 3</p> <p style="text-align: center;">1981</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <hr/> <p>N. 0° 06' E., beginning new measurement.</p> <p>Over gently rolling land.</p>