

DEPENDENT RESURVEY OF A PORTION  
OF THE SUBDIVISIONAL LINES,  
T. 38 N., R. 47 E., MDM, NEVADA

CHAINS	
	<p>from which</p> <p>An aluminum post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° W., 61 lks. dist., with aluminum cap mkd. RM T 38 N R 47 E S 5 40 ft. 1981 and an arrow pointing to the cor.</p> <p>An aluminum post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 66° E., 61 lks. dist., with aluminum cap mkd. RM T 38 N R 47 E S 4 40 ft. 1981 and an arrow pointing to the cor.</p>
53.00	Trail road, bears NNE. and SSW.
81.26	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., firmly set and showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 39 N., R. 47 E., executed concurrently under this same Group.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.</p> <p>N. 1° 59' E., bet. secs. 31 and 32.</p> <p>Over high rolling mountainous land, covered with sagebrush and native grass.</p>
14.80	Wash, 15 lks. wide, 1½ ft. deep, drains WNW.
29.30	Wash, 20 lks. wide, 1½ ft. deep, drains W.
40.10	<p>Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T38N R47E ¼ S 31 S 32  1981</p>
80.20	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T38N R47E S 30 S 29 S 31 S 32  1981</p>