

240

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 39 N., R. 47 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 39 N., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by,
U.S. Deputy Surveyors A.J. Hatch, J.H. Eaton and
J.C. Smyles, in 1872 and 1873.

From the corner of Tps. 38 and 39 N., Rs. 47 and 48 E.,
monumented with an iron post, 3 ins. diam., firmly set
in a mound of stone, with brass cap mkd. as described in
the field notes of the dependent resurvey of T. 39 N.,
R. 48 E., executed under Group No. 114. This corner is
identical with a U.S.G.S. triangulation station.

S. 88° 33' W., bet. secs. 1 and 36.

Over rolling land, covered with sagebrush and native
grass.

39.36 The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented with a
sandstone, 12x9x5 ins., plainly mkd. $\frac{1}{4}$ on the N. face,
firmly set in a mound of stone.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16
ins. in the ground to solid rock and in a mound of
stone, 3 ft. base to top, with aluminum cap mkd.

T39N R47E
S 36
 $\frac{1}{4}$ S 1
T38N

1981

Deposit the original cornerstone and set a steel fence
post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.

N. 89° 46' W., beginning new measurement.

Over rolling land.

40.10 The cor. of secs. 1, 2, 35 and 36, monumented with a
sandstone, 18x11x5 ins., plainly mkd. with 1 groove
on the E. face and 5 grooves on the W. face, firmly set
in a mound of earth.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24
ins. in the ground, with aluminum cap mkd.