6

244

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 39 N., R. 47 E., MDM, NEVADA

T. 39 N., R. 47 E., MDM, NEVADA
T39N R47E <u>5 32</u> 5 5 T38N
1981
Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.
From this corner, a well bears S. 14° 31' E., 10.46 chs. dist.
Fence, bears NW. and SE.
The cor. of secs. 5, 6, 31 and 32, monumented with a basalt stone, 16x6x6 ins.,plainly mkd. with 5 notches on the E. edge and 1 notch on the W. edge, loosely set in a mound of earth.
At the corner point
Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
T39N R47E S 31 S 32 S 6 S 5 T38N
1981
Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post. N. 89° 48' W., bet. secs. 6 and 31.
Over nearly level land, covered with sagebrush and native grass.
The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a basalt stone, $18x5x4$ ins., dimly mkd. $\frac{1}{4}$ on the N. face, loosely set in a mound of earth.
At the corner point
Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
$\begin{array}{rrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrr$
1981
Deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.