DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,

T. 39 N., R. 47 E., MDM, NEVADA CHAINS S. 86° 43' W., beginning new measurement. Over nearly level land. 25.50 Fence, bears NNW. and SSE. 37.75 The cor. of Tps. 38 and 39 N., Rs. 46 and 47 E., monumented with a basalt stone, 24x18x12 ins., plainly mkd. with 6 nothces on the N., S., E. and W. edges, firmly set in a mound of stone. At the corner point Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with aluminum cap mkd. T39N R46E R47E S 36|S 31 1|8 T38N 1981 Deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. This corner is located in a fence corner, from which fences bear N., NE. and W. DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 39 N., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of the Survey Executed by U.S. Deputy Surveyors, A.J. Hatch, J.H. Eaton and J.C. Smyles in 1872 and 1873, and the Resurvey Executed by U.S. Cadastral Engineer C.S. Swanholm, in 1930. From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 39 N., R. 48 E., executed under Group No. 114. N. 0° 52' E., bet. secs. 13 and 18. Over rolling land, covered with sagebrush and native grass. 40.30 The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 39 N., R. 48 E., executed under Group No. 114.