

252

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 47 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 47 E., MDM, NEVADA

---

Reestablishment of the Survey Executed by  
U.S. Deputy Surveyors A.J. Hatch, J.H. Eaton, and  
J.C. Smyles, in 1872 and 1873,  
and the Survey Executed by  
U.S. Deputy Surveyors E.C. McClellan and E.L. Bridges,  
in 1885.

---

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy.  
of the Tp.

N. 0° 03' W., bet. secs. 35 and 36.

Over gently rolling land, covered with sagebrush and  
native grass.

- 7.50 Willow Creek, S. channel, 20 lks. wide, 2 ft. deep,  
course SW.
- 20.30 Willow Creek, N. channel, 20 lks. wide, 2 ft. deep,  
course SW.
- 38.00 Improved gravel road, bears NE. and SW.
- 40.32 Point for the  $\frac{1}{4}$  sec. cor. of secs. 35 and 36, at  
proportionate distance; there is no remaining evidence  
of the original corner.
- Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 22  
ins. in the ground, with aluminum cap mkd.
- T39N R47E  
 $\frac{1}{4}$   
S 35|S 36
- 1981
- Set a steel fence post, 5 $\frac{1}{2}$  ft. long, alongside the  
aluminum post and raise a mound of stone, 3 ft. base, 2  
ft. high, W. of cor.
- From this cor., a U.S.C. & G.S. Bench Mark, monumented  
with a standard brass tablet set in concrete, with brass  
tablet mkd. "C-76 1934", bears N. 71° 34' E., 46.78  
chs. dist.
- 63.60 Telephone cable, underground, bears N. 80° E. and S. 80°  
W.
- 64.20 Trail road, bears E. and W.