

298

DEPENDENT RESURVEY OF THE MOUNT DIABLO BASE LINE,  
THROUGH A PORTION OF R. 41 E.

CHAINS

DEPENDENT RESURVEY OF THE MOUNT DIABLO BASE LINE,  
THROUGH A PORTION OF RANGE 41 EAST

Reestablishment of the Survey Executed by  
J.R. Glover and G.H. Perrin, U.S. Deputy Surveyors,  
in 1881.

From the standard cor. of Tps. 1 N., Rs. 40 and 41 E.,  
monumented with a blue limestone, 16x8x8 ins., firmly  
set in a mound of stone, plainly mkd. with 6 grooves on  
the W., N. and E. faces and T1N on the N. face,  
identical with N.P.D. triangulation station "MASTER,"  
as shown on Protraction Diagram No. 63. Hereafter,  
this cor. refers to the SW. cor. of sec. 31, T. 1 N.,  
R. 41 E., only.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

SC  
|T1N  
|R41E  
|S 31

1982

Deposit the original cornerstone and set a steel fence  
post, 5½ ft. long, alongside the aluminum post and  
raise a mound of stone, 3 ft. base, 2 ft. high, N. of  
cor.

S. 89° 31' E., along the S. bdy. of sec. 31.

Over gently rolling land, covered with sagebrush and  
scattered cacti.

4.524 The closing cor. of Tp. 1 S., Rs. 40 and 41 E.,  
hereinafter described.

40.14 Point for the standard ¼ sec. cor. of sec. 31, at  
proportionate distance; there is no remaining evidence  
of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 22  
ins. in the ground, with aluminum cap mkd.

SC  
T1N R41E  
¼ S 31

1982

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of  
cor.

57.20 Trail road, bears NW. and SE.