352

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 2 S., R. 40 E., MDM, NEVADA

CHAINS	
	N. 0° 37' E., beginning new measurement.
	Over gently rolling land.
39.85	The cor. of secs. 1 and 12, monumented with a basalt stone, 14x10x6 ins., loosely set in a mound of stone, plainly mkd. with 5 grooves on the S. face and 1 groove on the N. face, and is identical with N.P.D. triangulation station "PACE" as shown on Protraction Diagram No. 154, Unit No. 89.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T2S| R40E| S 1| S 12| 1982
	Deposit the original cornerstone alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 0° 59' E., along the E. bdy. of sec. 1.
	Over gently rolling land, covered with sagebrush and scattered cacti.
3.10	Improved gravel road, bears WNW. and ESE.
8.70	Improved gravel road, bears WNW. and ESE.
40.19	The E. ¼ sec. cor. of sec. 1, monumented with a basalt stone, 18x14x10 ins., firmly set 12 ins. in the ground, plainly mkd. ¼ on the W. face, with a mound of stone W. of cor.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T2S| R40E| ¼| S 1| 1982
	Deposit the original cornerstone alongside the aluminum post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

☆U.S. Government Printing Office: 1980—778-251/292