414

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 1 S., R. 40 E., MDM, NEVADA

CHAINS	
40.00	Point for the ¼ sec. cor. of sec. 32, falls in leaching pond, where it is impracticable to perpetuate a permanent monument.
69.81	Point for the closing cor. of secs. 4 and 5, T. 2 S., R. 40 E., as described in the field notes of the dependent resurvey of T. 2 S., R. 40 E., executed concurrently under this same Group.
80.00	Point for the cor. of secs. 32 and 33, falls in leaching pond where it is impracticable to perpetuate a permanent monument.
	N. 89° 48' W., along the S. bdy. of sec. 31.
	Over leaching pond.
3.50	Leave leaching pond, enter nearly level land, with no vegetation.
3.60	Point selected for the witness cor. of secs. 31 and 32.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	WC T1S R40E S 31 | S 32 → S 5 T2S 1982
3.70	Trail road on levee, bears NE. and SW.
29.87	The N. ¼ sec. cor. of sec. 5, T. 2 S., R. 40 E., monumented with an aluminum post, 2½ ins. diam., firmly set showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 2 S., R. 40 E., executed concurrently under this same Group.
40.00	Point for the ¼ sec. cor. of sec. 31, established at 360 chs. W. in departure from the cor. of secs. 35 and 36.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with aluminum cap mkd.
	T1S R40E ¼ S 31 T2S 1982
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
69.93	The closing cor. of secs. 5 and 6, T. 2 S., R. 40 E., monumented with an aluminum post, 2½ ins. diam., firmly set showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 2 S., R. 40 E., executed concurrently under this same Group.