DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 21 N., R. 47 E., MDM, NEVADA

35.96

Intersect the S. bdy. of sec. 33, T. 22 N., R. 47 E.

Point for the closing cor. of secs. 3 and 4.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with an aluminum cap mkd.

T22N R47E
S 33
S 4 | S 3
C | C
T21N R47E

1982

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the SE. cor. of sec. 33, T. 22 N., R. 47 E., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set, showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 22 N., R. 47 E., executed concurrently under this same Group, bears S. 88° 45' E., 2.17 chs. dist.

From this same corner, the cor. of secs. 3 and 4, monumented with an iron post, 2 ins. diam., firmly set, showing 8 ins. above ground, with brass cap mkd. as described in the field notes of T. 21 N., R. 47 E., executed under Group No. 91, bears N. 0° 09' W., 5.25 chs. dist. Hereafter, this cor. will function as an amended monument.

Add the marks AM and 1982 to the brass cap.

from which:

The cor. of secs. 33 and 34, T. 22 N., R. 47 E., (now an AM) hereinbefore described, bears N. 89 15 E., 0.91 chs. dist.

From the cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 2 ins. diam., firmly set, showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the subdivisional lines of T. 21 N., R. 47 E., executed under Group No. 91.

N. 0° 03' W., bet. secs. 4 and 5.

Over nearly level land, covered with scattered sagebrush.

39.93

Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.