

DEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
T. 22 N., R. 47 E., MDM, NEVADA

CHAINS	
	Over nearly level land, covered with scattered sagebrush.
5.31	The closing cor. of secs. 3 and 34, Tps. 21 and 22 N., R. 47 E., monumented with an aluminum post, 2½ ins. diam., firmly set, showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 21 N., R. 47 E., executed concurrently under this same Group.
40.10	<p>Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. Hereafter, this cor. will refer to sec. 33 only.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> T22N   R47E   ¼   S 33  </div> <p>1982</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
45.32	<p>Point for the W. ¼ sec. cor. of sec. 34, determined at 40.00 chs. in latitude from the closing cor. of secs. 3 and 34, Tps. 21 and 22 N., R. 47 E.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;">  T22N   R47E   ¼   S 34 </div> <p>1982</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p>
80.20	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a wooden post, 40 ins. long, 3 ins. square, with illegible scribing visible, loosely set in a mound of earth.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> T22N R47E  S 28 S 27  S 33 S 34 </div> <p>1982</p>