

67

COMPETITION SURVEY OF SECTION 34,
T. 22 N., R. 47 E., MDM, NEVADA

CHAINS

Point for the S. $\frac{1}{4}$ sec. cor. of sec. 34, established at 40.00 chs. in departure from the closing cor. of secs. 34 and 35 and on the N. bdy. of sec. 3, T. 21 N., R. 47 E.

Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T22N R47E

$\frac{1}{4}$ S 34

T21N

1982

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

From this corner, the N. $\frac{1}{4}$ sec. cor. of sec. 3, T. 21 N., R. 47 E., monumented with an iron post, 1 in. diam., firmly set, showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 21 N., R. 47 E., executed concurrently under this same Group, bears N. 89° 56' W., 5.34 chs. dist.

GENERAL DESCRIPTION

The land surveyed within Township 22 North, Range 47 East is about 5,600 to 5,900 ft. above sea level and is nearly level to rolling land. The soil is sandy clay loam along the level land and rocky in the higher elevations. The land is covered with scattered sagebrush.

There is an improved gravel road crossing from southwest to northeast, entering in sec. 31 and leaving in sec. 1.

Callaghan Creek enters the township in sec. 31 and leaves in sec. 4.

Principal users of the area are ranchers.

A windmill is located in sec. 10.
