

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 23 N., R. 39 E., MDM, NEVADA

CHAINS		
	<p>Set a steel fence post, 5½ ft. long, alongside the aluminum post.</p>	
	<hr/> <p>S. 89° 47' W., bet. secs. 5 and 32.</p>	
	<p>Over high rolling mountainous land, covered with sagebrush, native grass, scattered juniper and pinon pine.</p>	
18.50	<p>Ridge, bears N. and S.</p>	
40.30	<p>Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p>	
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p>	
	<p style="text-align: center;">T23N R39E $\frac{1}{4}$ $\frac{S\ 32}{S\ 5}$ T22N 1982</p>	
	<p>Set a steel fence post, 5½ ft. long, alongside the aluminum post.</p>	
69.50	<p>Wash, 30 lks. wide, 2 ft. deep, drains SW.</p>	
80.60	<p>The cor. of secs. 5, 6, 31 and 32, monumented with an unmarked basalt stone, 20X12X10 ins., firmly set in a mound of stone. This point correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.</p>	
	<p>At the corner point</p>	
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>	
	<p style="text-align: center;">T23N R39E $\frac{S\ 31\ \ S\ 32}{S\ 6\ \ S\ 5}$ T22N 1982</p>	
	<p>Deposit the unmarked stone and set a steel fence post, 5½ ft. long, alongside the aluminum post and raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p>	
	<hr/> <p>S. 88° 13' W., bet. secs. 6 and 31.</p>	
	<p>Over high rolling mountainous land, covered with sagebrush, native grass and scattered juniper.</p>	
38.90	<p>Ridge, bears N. and S.</p>	