

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 23 N., R. 39 E., MDM, NEVADA

CHAINS	
	<p style="text-align: center;">Reestablishment of the Survey Executed by E. L. Bridges, U. S. Deputy Surveyor, in 1882.</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 0° 09' W., bet. secs. 35 and 36.</p> <p>Over high rolling mountainous land, covered with sagebrush, pinon pine and scattered juniper.</p> <p>39.76 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T23N R39E $\frac{1}{4}$ S 35 S 36 1982</p> <p>Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post and raise a mound of stone, 5 ft. base, 3 ft. high, W. of cor.</p> <p>79.52 The cor. of secs. 25, 26, 35 and 36, monumented with a mound of stone, no marked stone found.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock over a cross (X) and in a mound of stone, 5 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T23N R39E S 26 S 25 S 35 S 36 1982</p> <p>Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set, showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 23 N., R. 40 E., executed under Group No. 572.</p> <p>S. 89° 38' W., bet. secs. 25 and 36.</p> <p>Over high rolling mountainous land, covered with sagebrush, native grass, scattered juniper and pinon pine.</p>