

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 23 N., R. 39 E., MDM, NEVADA

CHAINS	
	<div>T23N R39E</div> <div>S 23 S 24</div> <div>S 26 S 25</div> <div>1982</div> <div>Set a steel fence post, 5½ ft. long, alongside the aluminum post and raise a mound of stone, 5 ft. base, 3 ft. high, W. of cor.</div> <div></div> <div>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., firmly set, showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 23 N., R. 40 E., executed under Group No. 572.</div> <div>S. 89° 30' W., bet. secs. 24 and 25.</div> <div>Over high rolling mountainous land, covered with sagebrush, native grass and scattered juniper.</div> <div>4.50<div>Spur, slopes NW.</div></div> <div>11.50<div>Bladed road, in wash, bears NE. and SW: Wash drains NE.</div></div> <div>40.09<div>Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</div><div>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</div><div></div><div>T23N R39E</div><div>¼ S 24</div><div>¼ S 25</div><div>1982</div><div>Set a steel fence post, 5½ ft. long, alongside the aluminum post and raise a mound of stone, 5 ft. base, 2 ft. high, N. of cor.</div><div>66.80<div>Ridge, bears N. and S.</div></div><div>80.18<div>The cor. of secs. 23, 24, 25 and 26.</div><div></div><div>N. 0° 16' W., bet. secs. 23 and 24.</div><div>Over high rolling mountainous land, covered with sagebrush and native grass.</div><div>39.77<div>Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</div><div>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</div></div></div></div>