

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 22 N., R. 39 E., MDM, NEVADA

CHAINS

T22N
R38E R39E
 $\frac{1}{4}$
S 1|S 6

1983

Deposit the original cornerstone alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 0° 42' W., beginning new measurement.

Over mountainous land.

40.35

The cor. of Tps. 22 and 23 N., Rs. 38 and 39 E., monumented with an aluminum post, 2½ ins. diam., firmly set, showing 18 ins. above ground and in a mound of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 23 N., R. 39 E., concurrently resurveyed under this same Group.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 39 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
E. L. Bridges, U.S. Deputy Surveyor, in 1882.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 21 N., R. 39 E., executed under Group No. 476.

From this corner, a U.S.G.S. triangulation station and Bench Mark, monumented with a standard brass tablet set in concrete with brass tablet mkd. "34 RBR," bears S. 6° 04' E., 54.21 chs. dist.

N. 0° 48' W., bet. secs. 35 and 36.

Over rolling land, covered with sagebrush and cheatgrass.

34.50

Improved gravel road, bears WNW. and ESE.

39.83

Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T22N R39E
 $\frac{1}{4}$
S 35|S 36

1983