

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 39 E., MDM, NEVADA

CHAINS	<p>Set a steel fence post, 5½ ft. long, alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>From this corner, a U.S.G.S. Bench Mark, monumented with a standard brass tablet set in concrete with brass tablet mkd. "35 RBR," bears S. 60° 36' E., 23.95 chs. dist.</p>
79.66	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with aluminum cap mkd.</p> <div>T22N R39E S 26 S 25 S 35 S 36</div> <p>1983</p> <p>Set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., firmly set, showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 22 N., R. 40 E., executed under Group No. 572.</p> <p>N. 89° 53' W., bet. secs. 25 and 36.</p> <p>Over rolling land, covered with sagebrush and cheatgrass.</p>
21.40	<p>Wash, 30 lks. wide, 2 ft. deep, drains SSE.</p>
29.80	<p>Improved gravel road, bears N. and S.</p>
40.65	<p>Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd.</p> <div>T22N R39E S 25 ¼ S 36</div> <p>1983</p> <p>Set a steel fence post, 5½ ft. long, alongside the aluminum post.</p>
58.60	<p>Spur, projects S.</p>
81.30	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/>