

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 39 E., MDM, NEVADA

CHAINS		
	<p>Set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an aluminum post, 2½ ins. diam., firmly set, showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 22 N., R. 40 E., executed under Group No. 572.</p> <p>N. 89° 56' W., bet. secs. 13 and 24.</p> <p>Over mountainous land, covered with sagebrush, native grass, heavy juniper and pinon pine.</p>	
36.00	Wash, 10 lks. wide, 6 ins. deep, drains S.	
40.39	<p>Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T22N R39E $\frac{1}{4}$ $\frac{S\ 13}{S\ 24}$ 1983</p>	
70.90	<p>Set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <p>Ridge, bears NNW. and SSE.</p>	
80.78	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 0° 39' W., bet. secs. 13 and 14.</p> <p>Over mountainous land, covered with scattered sagebrush, juniper and pinon pine.</p>	
16.20	Ridge, bears SE. and NW.	
39.83	<p>Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T22N R39E $\frac{1}{4}$ S 14 S 13 1983</p>	
79.66	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.	