

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 34 N., R. 69 E., MDM, NEVADA

CHAINS

Deposit the original cornerstone and reset the steel fence post, 5 ft. long, alongside the iron post.

---

S. 89° 58' W., bet. secs. 5 and 32.

Over nearly level land, covered with sagebrush and native grass.

39.97

The  $\frac{1}{4}$  sec. cor. of secs. 5 and 32, monumented with a limestone, 14X10X8 ins., firmly set 8 ins. in a mound of earth, mkd.  $\frac{1}{4}$  on N. face, with a steel fence post alongside.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T35N R69E

	S 32
$\frac{1}{4}$	S 5
	T34N

1982

Deposit the original cornerstone and reset the steel fence post, 5 ft. long, alongside the iron post.

---

WEST, beginning new measurement.

Over nearly level land.

40.01

The cor. of secs. 5, 6, 31 and 32, monumented with a limestone, 20X16X4 ins., firmly set 10 ins. in a mound of earth, mkd. with 5 notches on the E. edge and 1 notch on the W. edge, with a steel fence post alongside.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T35N R69E

S 31	S 32
S 6	S 5
	T34N

1982

Deposit the original cornerstone and reset the steel fence post, 5 ft. long, alongside the iron post.

---

S. 89° 57' W., bet. secs. 6 and 31.

Over nearly level land, covered with sagebrush and native grass.