

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 17 N., R. 64 E., MDM, NEVADA

CHAINS

31.30

Top of spur, slopes NE.

44.52

The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., firmly set, showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 17 N., R. 64 E., executed under Group No. 257.

Add the marks 1983 to the brass cap.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 17 N., R. 64 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
E. B. Monroe and A. G. Bateman, U.S. Deputy Surveyors,
in 1872.

From the cor. of Tps. 17 and 18 N., Rs. 64 and 65 E., monumented with a steel rebar, 5/8 ins. diam., 16 ins. long, firmly set in a well embedded mound of stone, and is accepted as a careful and faithful perpetuation of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T18N
R64E R65E
S 36 | S 31
S 1 | S 6
T17N

1983

Deposit the rebar alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

S. 89° 09' W., bet. secs. 1 and 36.

Over rolling land, covered with scattered sagebrush, pinon pine and juniper.

8.00

Duck Creek, 5 ft. wide, 3 ft. deep, course irregularly N.

38.89

Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.