DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 41 N., R. 48 E., MDM, NEVADA

CHAINS Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post. N. 84° 43' W., along the N. bdy. of sec. 13. Over mountainous land, covered with scattered sagebrush. 40.17 Point for the 1 sec. cor. of sec. 13 only, established at 40.00 chs. in departure from the cor. of secs. 13 and 18, on the E. bdy. of the Tp. Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd. S 13 **T41N R48E** 1983 48.82 The cor. of secs. 7, 12, 13 and 18, of the Hatch and Eaton Survey, monumented with a mound of stone. No marked stone found. This point is harmoniously related to other existing original cors. and is accepted as the best available evidence of the position of the original corner. This corner now refers to the cor. of secs. 7 and 12, only. At the corner point Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd. T41N R48E | R49E S 12 | S 7 S 13 **T41N R48E** 1982 Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post. N. 0° 22' E., bet. secs. 7 and 12. Over mountainous land, covered with scattered sagebrush. The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented with a trachyte stone, 16X10X8 ins., firmly set and exposed 10 32.75 ins. above the ground, dimly mkd. $\frac{1}{4}$ on W. face. (Record wooden post.) At the corner point Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.