

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,
THROUGH RANGE 63 EAST, MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL
NORTH,
THROUGH RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
E. B. Monroe and A. J. Bateman, U.S. Deputy Surveyors,
in 1872.

From the standard cor. of Tps. 11 N., Rs. 63 and 64 E.,
monumented with an iron post, 2½ ins. diam., firmly set
in a mound of stone, showing 6 ins. above ground, with
brass cap mkd. as described in the field notes of the
dependent resurvey of T. 11 N., R. 64 E., executed
under Group No. 420.

N. 89° 14' W., along the S. bdy. of sec. 36.

Over rolling land, covered with medium juniper, pinon
pine, sagebrush, native grass and sparse cacti.

39.55 The standard ¼ sec. cor. of sec. 36, monumented with
the decayed remains of a juniper post, loosely set in a
mound of stone, with a steel fence post firmly set
alongside.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

SC
T11N R63E
¼ S 36

1983

Bury the original wooden post and reset the steel fence
post, 5½ ft. long, alongside the aluminum post and
raise a mound of stone, 3 ft. base, 2 ft. high, N. of
cor.

S. 89° 55' W., beginning new measurement.

Over rolling land.

15.50 Trail road, bears NW. and SE.

40.03 The standard cor. of secs. 35 and 36, monumented with
the decayed remains of a juniper post, loosely set in a
mound of stone, with a steel fence post firmly set
alongside.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24
ins. in the ground, with aluminum cap mkd.