

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,
THROUGH RANGE 63 EAST, MDM, NEVADA

CHAINS	
	<p style="text-align: center;">SC T11N R63E <u>¼ S 32</u></p> <p style="text-align: center;">1983</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
79.18	<p>Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">SC T11N R63E <u>S 31 S 32</u></p> <p style="text-align: center;">1983</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<hr/> <p>N. 89° 03' W., along the S. bdy. of sec 31.</p> <p>Over mountainous land, covered with heavy juniper, pinon pine, mountain mahogany, sagebrush and native grass.</p>
17.30	Ridge, bears NNE. and SSW.
35.90	Creek, 10 lks. wide, 4 ins. deep, course irregularly S.
39.59	<p>The standard ¼ sec. cor. of sec. 31, monumented with a limestone, 16X8X6 ins., firmly set in a mound of earth, plainly mkd. ¼ on the N. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">SC T11N R63E <u>¼ S 31</u></p> <p style="text-align: center;">1983</p> <p>Deposit the original cornerstone alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<hr/> <p>S. 89° 59' W., beginning new measurement.</p> <p>Over mountainous land.</p>
32.70	Spur, slopes SSW.