

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 18 S., R. 59 E., MDM, NEVADA

CHAINS	
41.10	<p>Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented with a limestone, 12X6X4 ins., firmly set in a mound of stone, plainly mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18S R59E R60E $\frac{1}{4}$ S 25 S 30</p> <p style="text-align: center;">1984</p> <p>Bury the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. $0^{\circ} 18'$ E., beginning new measurement.</p> <p>Over nearly level land.</p>
40.97	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a limestone, 8X8X6 ins., firmly set in a mound of stone, plainly mkd. with 4 notches on N. edge and no other marks visible (stone was chipped on S. edge).</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18S R59E R60E S 24 S 19 S 25 S 30</p> <p style="text-align: center;">1984</p> <p>Bury the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E. A. Carter, in 1881.</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.</p> <p>N. $1^{\circ} 21'$ E., bet. secs. 35 and 36.</p>