

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 38 N., R. 61 E., MDM, NEVADA

CHAINS

T38N R61E

S 23 | S 24

S 26 | S 25

1983

Reset the wooden post and steel pipe alongside the iron post.

---

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 38 N., R. 62 E., executed concurrently under this same Group.

N.  $89^{\circ} 13'$  W., bet. secs. 24 and 25.

Over gently rolling land, through scattered sagebrush.

21.20 Old telephone line, bears NW. and SE.

22.30 Humboldt River, 50 lks. wide, 6 ins. deep, course NW.

22.90 Abandoned railroad grade, bears NW. and SE.

23.40 Fence corner, from which fences bears SE., NW. and W., along fence.

40.04 The  $\frac{1}{4}$  sec. cor. of secs. 24 and 25, determined at the corner of fences, bearing NNW. and irregularly E. This fence corner is locally recognized as the cor. and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T38N R61E

$$\frac{1}{4} \frac{S 24}{S 25}$$

1983.

---

N.  $89^{\circ} 42'$  W., beginning new measurement.

Over rolling land.

40.82 The cor. of secs. 23, 24, 25 and 26.

---

N.  $0^{\circ} 06'$  W., bet. secs. 23 and 24.

Over rolling land, through scattered sagebrush.