DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 38 N., R. 62 E., MDM, NEVADA

CHAINS	
	Set a steel fence post, 5½ ft. long, alongside the iron post.
70.80	Enter rolling land.
78.10	Fence, bears S. and N., 0.04 chs. dist., to fence corner, from which fences bear W. and S.
78.82	The cor. of secs. 4, 5, 32 and 33, monumented with a sandstone, 18X8X8 ins., plainly mkd. with 4 notches on E. edge and 2 notches on W. edge with a cross (X) on top, firmly set in a mound of earth and in fence, bearing E. and W. This corner now refers to secs. 4 and 5, and sec. 33, T. 38½ N., R. 62 E., only. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T39N R62E S 32 T38½N S 5 S 33 S 4 R62E T38N R62E 1983 Deposit the original cornerstone alongside the iron post. From this corner, a U.S.G.S. Bench Mark, monumented with a standard brass tablet, firmly set in concrete, with brass tablet mkd. "136 DOR 1965," bears N. 85° 37' E., 0.20 chs. dist.
	N. 89° 19' W., along the N. bdy. of sec. 5. Over rolling land, through scattered sagebrush and crested wheat grass, along fence.
2.20	Paved road, bears N. 16¾° E. and N. 16¾° W.
2.70	Power line, lines bears N. 16¾° E. and S. 16¾° W.
32.54	Point for the Maxson ¼ sec. cor. of secs. 5 and 32, determined latitudinally in an old fence, bearing E. and W. and longitudinally at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to the S. ¼ sec. cor. of sec. 32, T. 39 N., R. 62 E., only. CORNER NOT MONUMENTED
40.36	Point for the ¼ sec. cor. of secs. 5 and 32, determined latitudinally in an old fence, bearing E. and W. and longitudinally at proportionate distance; there is no remaining evidence of the original corner.