

426

DEPENDENT RESURVEY OF THE SECOND STANDARD
PARALLEL NORTH, THROUGH A PORTION OF RANGE
36 EAST, MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE SECOND STANDARD
PARALLEL NORTH, THROUGH A PORTION OF RANGE
36 EAST, MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
G. W. Conkling and T. K. Stewart,
U.S. Deputy Surveyors, in 1883.

From the standard cor. of secs. 33 and 34, identical with the Nevada Planning Division of the Nevada Highway Department station "STAD 1953," monumented with a porphyry stone, 14X10X3 ins., firmly set in a mound of stone, plainly mkd. with 3 notches on E. and W. edges and SC on N. face, with a steel fence post, firmly set showing 4½ ft. above ground alongside.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

SC
T11N R36E
S 33 | S 34

1984

Deposit the original cornerstone and reset the steel fence post, 5½ ft. long, alongside the aluminum post and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.

N. 88° 48' W., along the S. bdy. of sec. 33.

Over rolling land, covered with medium greasewood and scattered Brigham tea.

12.64 Intersect U.S.G.S. triangulation station "RED," monumented with a standard brass tablet firmly set in concrete, with brass tablet mkd. "RED 1944."

32.30 Wash, 15 lks. wide, 3 ft. deep, drains NNW.

40.19 The standard ¼ sec. cor. of sec. 33, monumented with a granite stone, 18X11X10 ins., firmly set in a mound of stone, plainly mkd. ¼ on N. face, with a steel fence post, firmly set showing 4½ ft. above ground alongside.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.

SC
T11N R36E
¼ S 33

1984

Deposit the original cornerstone and reset the steel fence post, 5½ ft. long, alongside the aluminum post.