

428

DEPENDENT RESURVEY OF THE SECOND STANDARD  
PARALLEL NORTH, THROUGH A PORTION OF RANGE  
36 EAST, MDM, NEVADA

CHAINS 61.30	Ridge, bears NW. AND SE.
67.40	Ridge, bears NNW. and SSE.
77.20	Spur, projects NNW.
79.44	Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.  Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.  SC T11N R36E <u>S 31   S 32</u>  1984  Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  <hr/> N. $88^{\circ} 02'$ W., along the S. bdy. of sec. 31.  Over rolling land, covered with medium greasewood and scattered Brigham tea.
4.10	Spur, projects WNW.
20.85	The closing cor. of secs. 3 and 4, T. 10 N., R. 36 E., hereinafter described.
39.72	The standard $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a granite stone, 14X10X8 ins., loosely set in a mound of earth, plainly mkd. $\frac{1}{4}$ on N. face, with a steel fence post, firmly set and showing $4\frac{1}{2}$ ft. above ground alongside.  At the corner point  Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.  SC T11N R36E <u><math>\frac{1}{4}</math> S 31</u>  1984  Bury the original cornerstone and reset the steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.  <hr/> N. $89^{\circ} 29'$ W., beginning new measurement.