DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH, THROUGH A PORTION OF RANGE 35 EAST, MDM, NEVADA

 	35 EAST, MDM, NEVADA
CHAINS	N. 89° 43' W., along the S. bdy. of sec. 34.
	Over rolling land, covered with medium greasewood and scattered Brigham tea.
6.20	The closing cor. of Tps. 10 N., Rs. 35 and 36 E., hereinafter described.
27.50	Fence, bears S. 42° E. and N. 42° W.
40.49	The standard $\frac{1}{4}$ sec. cor. of sec. 34, monumented with the decayed remains of a wooden post, 1 in. diam., 10 ins. long, with illegible scribe marks visible, wired to a steel fence post, showing $4\frac{1}{2}$ ft. above ground.
	At the corner point
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	SC T11N R35E ½ S 34
	1984
	Deposit the original wooden post and reset the steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.
	DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 10 N., R. 35 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by G. W. Conkling and T. K. Stewart U.S. Deputy Surveyors, in 1883.

From the cor. of Tps. 9 and 10 N., Rs. 35 and 36 E., monumented with a granite stone, 22X18X12 ins., mkd. with 6 notches on N., S., E. and W. edges, firmly set in a mound of stone. Hereafter, this corner will refer to Tps. 9 and 10 N., Rs. 35 E. only.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.