## 443

## SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 10 N., R. 36 E., MDM, NEVADA

T. 10 N., R. 36 E., MDM, NEVADA		
	CHAINS	N. 0° 01' W., bet. secs. 2 and 3.
		Over rolling land, covered with medium undergrowth.
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
		Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
		T10N R36E
		s 3 s 2
		1984
		Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.
	80.00	Point for the 80 1/16 sec. cor. of secs. 2 and 3.
		Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
		1/16 s 3 s 2
		80
		1984
		Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.
į	100.00	Point for the 100 1/16 sec. cor. of secs. 2 and 3.
		Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
		1/16 s 3 s 2
		100
		1984
		Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.
	116.16	Intersect the Second Standard Parallel North.
	٠.	Point for the closing cor. of secs. 2 and 3.
		Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
İ		