

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 N., R. 36 E., MDM, NEVADA

CHAINS	
	From this corner, U.S.C. & G.S. Bench Mark, monumented with a standard brass tablet firmly set in concrete, with tablet mkd. "P 131 1934," bears N. 32° 49' E., 27.59 chs. dist.
42.00	Trail road, bears E. and W.
43.30	Wash, 10 lks. wide, 1 ft. deep, drains W.
78.70	Spur, projects W.
80.00	Point for the 80 1/16 sec. cor. of secs. 3 and 4. Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd. 1/16 S 4 S 3 80 1984
100.00	Point for the 100 1/16 sec. cor. of secs. 3 and 4. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. 1/16 S 4 S 3 100 1984 Set a steel fence post, 5½ ft. long, alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
114.20	Trail road, bears NW. and SE.
118.90	Intersect the Second Standard Parallel North. Point for the closing cor. of secs. 3 and 4. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T11N R36E S 31 S 4 S 3 T10N R36E CC 1984 Set a steel fence post, 5½ ft. long, alongside the aluminum post. From this corner, the standard ¼ sec. cor. of sec. 31, T. 11 N., R. 36 E., hereinbefore described, bears N. 88° 02' W., 18.87 chs. dist.