

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 N., R. 36 E., MDM, NEVADA

| CHAINS | |
|--------|---|
| | T10N R36E S 5 ¹ / ₄ S 4 1984 |
| 44.80 | Trail road, bears NW. and SE. |
| 59.70 | Spur, projects E. |
| 80.00 | Point for the 80 1/16 sec. cor. of secs. 4 and 5. Set an aluminum post, 30 ins. long, 2 ¹ / ₂ ins. diam., 24 ins. in the ground, with aluminum cap mkd. 1/16 S 5 ¹ / ₄ S 4 80 1984 Set a steel fence post, 5 ¹ / ₂ ft. long, alongside the aluminum post. |
| 100.00 | Point for the 100 1/16 sec. cor. of secs. 4 and 5. Set an aluminum post, 30 ins. long, 2 ¹ / ₂ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd. 1/16 S 5 ¹ / ₄ S 4 100 1984 |
| 120.09 | Intersect the Second Standard Parallel North. Point for the closing cor. of secs. 4 and 5. Set an aluminum post, 30 ins. long, 2 ¹ / ₂ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T11N R35E S 36 S 5 ¹ / ₄ S 4 T10N R36E CC 1984 Set a steel fence post, 5 ¹ / ₂ ft. long, alongside the aluminum post. From this corner, the standard cor. of Tps. 11 N., Rs. 35 and 36 E., hereinbefore described, bears S. 89° 31' E., 19.80 chs. dist. Land, rolling to mountainous. Soil, rocky clay. Undergrowth, shadscale Brigham tea, greasewood and native grass. |