460

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 10 N., R. 36 E., MDM, NEVADA

CHAINS Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post. Intersect the E. bdy. of sec. 1, T. 10 N., R. 35 E. 65.68 Point for the closing cor. of secs. 6 and 7, NORTH, 0.5 lks. from the tangent. Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with aluminum cap mkd. T10N R35E R36E S $1 \begin{vmatrix} S & 6 \\ S & 7 \end{vmatrix}$ CC Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post. From this corner, the cor. of secs. 1 and 12, T. 10 N., R. 35 E., hereinbefore described, bears S. 1 $^{\circ}$ 09' E., 15.82 chs. dist. Land, rolling. Soil, rocky clay. Undergrowth, native grass, Brigham tea and greasewood. Point for the W. $\frac{1}{4}$ sec. cor. of sec. 7, is at midpoint between closing cors. and on the E. bdy. of sec. 12, T. 10 N., R. 35 E. Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T10N R35E R36E Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor. From this corner, the E. $\frac{1}{4}$ sec. cor. of sec. 12, T. 10 N., R. 35 E., hereinbefore described, bears S. 1°09' E., 15.11 chs. dist. Point for the W. $\frac{1}{4}$ sec. cor. of sec. 6, is at 40 chs. in latitude from the closing cor. of secs. 6 and 7, and on the east bdy. of sec. 1, T. 10 N., R. 35 E.