

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 10 N., R. 36 E., MDM, NEVADA

	CHAINS	N. 0° 03' W., bet. secs. 5 and 6.  Over rolling land, covered with medium undergrowth.
4.10		Fence, bears N. 35 $\frac{3}{4}$ ° W. and S. 35 $\frac{3}{4}$ ° E.
25.20		Trail road, bears ESE. and WNW.
40.00		Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.  Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.  T10N R36E $\frac{1}{4}$ S 6 $\frac{1}{2}$ S 5  1984  Set a steel fence post, 5 $\frac{1}{2}$ ft. long, alongside the aluminum post.
71.70		Trail road, bears E. and W.
80.00		Point for the 80 $\frac{1}{16}$ sec. cor. of secs. 5 and 6.  Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.  $\frac{1}{16}$ S 6 $\frac{1}{2}$ S 5 80  1984  Set a steel fence post, 5 $\frac{1}{2}$ ft. long, alongside the aluminum post.
100.00		Point for the 100 $\frac{1}{16}$ sec. cor. of secs. 5 and 6.  Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.  $\frac{1}{16}$ S 6 $\frac{1}{2}$ S 5 100  1984  Set a steel fence post, 5 $\frac{1}{2}$ ft. long, alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
121.60		Intersect the Second Standard Parallel North.  Point for the closing cor. of secs. 5 and 6.  Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.