

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 22 N., R. 18 E., MDM, NEVADA

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T22N
R18E R19E
¼
S 1 | S 6

1984

Bury the original cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post.

From this corner, a U.S.G.S. Bench Mark, monumented with a standard brass tablet, firmly set in concrete, with brass tablet mkd. "20 JD 1955," bears S. 9° 46' W., 10.62 chs. dist.

N. 0° 37' W., beginning new measurement.

Over rolling land.

16.60 Trail road, bears NE. and SW.

30.60 Trail road, bears NW. and SE.

39.94 The cor. of Tps. 22 and 23 N., Rs. 18 and 19 E., monumented with an iron post, 3 ins. diam., firmly set and exposed 6 ins. above the ground, at the cor. of fences bearing N. and W., with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy. of T. 23 N., R. 19 E., executed under Group No. 13.

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISIONAL LINES,
T. 22 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
A. J. Hatch, W. W. Skinner and C. S. Preble,
U.S. Deputy Surveyors
in 1874, and
the Survey Executed by T. K. Stewart,
U.S. Deputy Surveyor in 1900.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.

N. 0° 50' W., bet. secs. 35 and 36.

Over gently rolling land, through scattered sagebrush, native grass and juniper.