

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISIONAL LINES,
T. 22 N., R. 18 E., MDM, NEVADA

CHAINS		
	<p>An aluminum post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground and in a collar of stone, 3 ft. base to top, for a reference monument, bears N. 45° W., 14.0 ft. dist., with aluminum cap mkd. T 22 N R 18 E RM S 6 14 Ft. 1984 and an arrow pointing to the true corner.</p>	
37.50	<p>From the cor. of secs. 4, 5, 8 and 9. N. 89° 33' W., bet. secs. 5 and 8. Over mountainous land, through scattered sagebrush, buckbrush and native grass; over W. slope of mountain. Spur, slope SW.</p>	
37.67	<p>Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd.</p>	
75.34	<p style="text-align: center;">T22N R18E ¼ $\frac{S \ 5}{S \ 8}$ 1984</p> <p>The cor. of secs. 5, 6, 7 and 8.</p>	
21.06	<p>N. 89° 32' W., bet. secs. 6 and 7. Over rolling land, through scattered sagebrush, buckbrush, Brigham tea and native grass. Intersect the Nevada-California State Line. Point for the closing cor. of secs. 6 and 7. Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T22N R18E CAL $\frac{S \ 6}{S \ 7}$ CC 1984</p> <p>From this corner, the original closing cor., monumented with a granite stone, 20X10X8 ins., firmly set in a mound of stone, plainly mkd. 5 notches on S. edge, 1 notch on N. edge and CC on E. face, bears N. 89° 32' W., 0.07 chs. dist. This corner will hereafter function as an amended monument. Add the marks AM and bury the stone 6 ins. below the surface of the ground.</p>	