

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 35 N., R. 69 E., MDM, NEVADA

CHAINS		
40.12	<p>N. 0° 11' E., beginning new measurement.</p> <p>Over rolling land.</p> <p>The cor. of secs. 1, 6, 7 and 12, monumented with a limestone, 24X10X7 ins., firmly set in a mound of stone, plainly mkd. with 1 groove on N. face and 5 grooves on S. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R69E R70E S 1   S 6 S 12   S 7</p> </div> <p>1984</p> <p>Bury the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post.</p> <p>From this corner, a trapstone, 18X13X6 ins., firmly set in a mound of stone, plainly mkd. with 5 grooves on the S. face and 1 groove on the N. face, bears S. 17° 58' E., 2.50 chs. dist. This corner now becomes an amended monument. Add the marks AM to cornerstone and bury in place. This is a corner of no record.</p>	
31.20 40.08	<p>N. 0° 12' W., bet. secs. 1 and 6.</p> <p>Over rolling land, covered with scattered sagebrush.</p> <p>Draw, drains SSW.</p> <p>The ¼ sec. cor. of secs. 1 and 6, monumented with a limestone, 16X8X6 ins., firmly set in a mound of stone, plainly mkd. ¼ on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R69E R70E ¼ S 1   S 6</p> </div> <p>1984</p> <p>Bury the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post.</p>	