

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 35 N., R. 69 E., MDM, NEVADA

<p>CHAINS</p>	<p>Set a steel fence post, 5½ ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>From this corner, the standard ¼ sec. cor. of sec. 36, T. 36 N., R. 68 E., hereinbefore described, bears N. 89° 38' W., 1.47 chs. dist.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 35 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of the Survey Executed by U.S. Deputy Surveyor W. B. Colwell, in 1909 and 1910.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp.</p> <p>N. 89° 58' W., bet. secs. 25 and 36.</p> <p>Over rolling land, covered with scattered sagebrush.</p> <p>39.98 The ¼ sec. cor. of secs. 25 and 36, monumented with a quartzite stone, 12X8X8 ins., firmly set in a mound of earth, showing 4 ins. above ground, plainly mkd. ¼ on N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R69E ¼ $\frac{S\ 25}{S\ 36}$</p> <p style="text-align: center;">1984</p> <p>Bury the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post.</p> <hr/> <p>N. 89° 59' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>40.05 The cor. of secs. 25, 26, 35 and 36, monumented with a quartzite stone, 20X8X6 ins., firmly set in a mound of stone, plainly mkd. with 1 notch on E. edge and 1 notch on S. edge.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
---------------	---