

DEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
T. 35 N., R. 69 E., MDM, NEVADA

CHAINS	
	<p style="text-align: center;">T35N R69E <math>\frac{1}{4}</math> S 2   S 1  1984</p>
	<p>Bury the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post.</p>
	<hr/> <p>N. 0° 01' W., beginning new measurement.</p>
	<p>Over rolling land.</p>
28.40	<p>Wash, 120 lks. wide, 6 ft. deep, drains WSW.</p>
30.40	<p>Wash, 90 lks. wide, 10 ft. deep, drains WSW.</p>
38.75	<p>Intersect the Seventh Standard Parallel North.</p>
	<p>The closing cor. of secs. 1 and 2, monumented with a limestone, 26X10X8 ins., firmly set in a mound of stone, mkd. with 1 groove on the E. face, 5 grooves on the W. face and CC on the S. face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R69E S 35 S 2   S 1 T35N R69E CC  1984</p>
	<p>Bury the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post.</p>
	<p>From this corner, the standard <math>\frac{1}{4}</math> sec. cor. of sec. 35, T. 36 N., R. 69 E., monumented with an iron post, 2½ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Seventh Standard Parallel North, through Range 69 East, executed concurrently under this same Group, bears N. 89° 53' E., 1.10 chs. dist.</p>
	<hr/> <p>Point for the N. <math>\frac{1}{4}</math> sec. cor. of sec. 1, is at midpoint between the closing cors. and on the Seventh Standard Parallel North.</p>