

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 35 N., R. 69 E., MDM, NEVADA

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36N R69E
 $\frac{1}{4}$ S 1
T35N R69E

1984

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.

From this corner, the standard cor. of secs. 35 and 36, T. 36 N., R. 69 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Seventh Standard Parallel North, through Range 69 East, executed concurrently under this same Group, bears N. $89^{\circ} 38'$ E., 0.97 chs. dist.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the survey of the east 2 miles of the N. bdy. of T. 34 N., R. 69 E., executed under Group No. 604.

This corner is identical with BLM Tellurometer Traverse Station as published on Nevada Protraction Diagram No. 31, Unit No. 26, established under Group No. 389.

N. $0^{\circ} 04'$ W., bet. secs. 34 and 35.

Over nearly level land, covered with scattered sagebrush.

39.98 The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, monumented with a limestone, 18X10X4 ins., firmly set in a mound of earth, showing 6 ins. above ground, with no marks visible. This limestone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35N R69E
 $\frac{1}{4}$
S 34 | S 35

1984

Bury the unmarked cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.