

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 35 N., R. 69 E., MDM, NEVADA

40.07
CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with a limestone, 24X8X6 ins., firmly set in a mound of earth, showing 10 ins. above ground, plainly mkd. $\frac{1}{4}$ on W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35N R69E

$\frac{1}{4}$

S 3 | S 2

1984

Bury the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.

From this corner, a limestone, 16X10X10 ins., firmly set in a mound of stone, showing 5 ins. above ground, mkd. $\frac{1}{4}$ on the W. face, bears S. $23^{\circ} 36' W.$, 2.29 chs. dist. This corner now becomes an amended monument. Add the marks AM to cornerstone and bury in place. This is a corner of no record.

NORTH, beginning new measurement.

Over nearly level land.

- 8.90 Trail road, bears S. $20^{\circ} W.$ and N. $20^{\circ} E.$
- 11.30 Wash, 80 lks. wide, 6 ft. deep, drains S. $70^{\circ} W.$
- 19.80 Wash, 110 lks. wide, 10 ft. deep, drains S. $70^{\circ} W.$
- 27.90 Wash, 110 lks. wide, 10 ft. deep, drains S. $60^{\circ} W.$
- 32.10 Wash, 140 lks. wide, 4 ft. deep, drains S. $60^{\circ} W.$
- 39.15 Intersect the Seventh Standard Parallel North.

The closing cor. of secs. 2 and 3, monumented with a limestone, 20X12X3 ins., firmly set in a mound of stone, mkd. with 2 grooves on the E. face, 4 grooves on the W. face and CC on the S. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36N R69E

S 34

S 3 | S 2

T35N R69E

CC

1984