

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 35 N., R. 69 E., MDM, NEVADA

CHAINS

Bury the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.

From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 36 N., R. 69 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Seventh Standard Parallel North, through Range 69 East, executed concurrently under this same group, bears S. $89^{\circ} 21' E.$, 0.81 chs. dist.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 2 is at midpoint between the closing cors. and on the Seventh Standard Parallel North.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36N R69E
 $\frac{1}{4}$ S 2
T35N R69E

1984

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.

From this corner, the standard cor. of secs. 34 and 35, T. 36 N., R. 69 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Seventh Standard Parallel North, through Range 69 East, executed concurrently under this same Group, bears S. $89^{\circ} 24' E.$, 0.68 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west 4 miles of the N. bdy. of T. 34 N., R. 69 E., executed under Group No. 604.

NORTH, bet. secs. 33 and 34.

Over nearly level land, covered with scattered sagebrush and greasewood.

40.08

The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with a mound of earth and broken glass. This point correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.