

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 35 N., R. 69 E., MDM, NEVADA

CHAINS

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 4 is at midpoint between the closing cors. and on the Seventh Standard Parallel North.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36N R69E
 $\frac{1}{4}$ S 4
T35N R69E

1984

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.

From this corner, the standard cor. of secs. 32 and 33, T. 36 N., R. 69 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Seventh Standard Parallel North, through Range 69 East, executed concurrently under this same Group, bears S. $89^{\circ} 26' E.$, 1.00 chs. dist.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west 4 miles of the N. bdy. of T. 34 N., R. 69 E., executed under Group No. 604.

N. $0^{\circ} 04' W.$, bet. secs. 31 and 32.

Over nearly level land, covered with scattered sagebrush.

- 0.20 Wash, 10 lks. wide, 1 ft. deep, drains N. $80^{\circ} E.$
- 12.40 Trail road, bears S. $55^{\circ} E.$ and N. $55^{\circ} W.$
- 18.20 Wash, 10 lks. wide, 2 ft. deep, drains E.
- 40.02 The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented with a limestone, 20X12X4 ins., firmly set in a mound of earth, showing 8 ins. above ground, plainly mkd. $\frac{1}{4}$ on W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35N R69E
 $\frac{1}{4}$
S 31 | S 32

1984